

**DECLARATION OF PERFORMANCE**

No. **300\_DOP\_Coem**

1. Unique identification code of the product type:  
**Dry-pressed ceramic tiles, with water absorption  $E_b > 10\%$**
2. Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $E_b > 10\%$**
3. Intended use(s)  
**For internal walls**
4. Name or registered trade mark, and contact address of the manufacturer  
**Coem SpA, Via Cameazzo, 25 Fiorano Modenese (MO)**
5. N.A.
6. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
7. Name and identification number of notified laboratory, if relevant N.A.  
 Task(s) carried out N.A.  
 AVCP system N.A.  
 Document issued and date of issue N.A.
8. N.A.
9. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411: 2012
- Cadmium*	NPD	
- Lead *	NPD	
Breaking strength Thickness $\geq 7.5$ mm	> 600 N	
Breaking strength Thickness < 7.5 mm	> 200 N	
Slipperiness**	NPD	
Tactility ***	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	NPD	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	NPD	

\* Only necessary in the case of materials that come into contact with foodstuffs or when required by corresponding national statutory regulations


\*\*Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification.

\*\*\*Only for tactile floorings, meaning if requested for blind and visually impaired: as a description of the surface

10. The performance of the product identified in point 1 is in conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

**ING. ELISA TONELLI (QM)**  
 Name and function



Signature **COEM S.p.A.**  
 Sede Legale: Via Cameazzo, n. 25  
 41042 Fiorano Mod.se (Mo)  
 Sede Amm.va: Via Stradone Secchia, n. 32  
 42014 ROTEGLIA (RE)  
 Tel. 0536 993111 - Fax 0536 993248  
 Cod.Fisc./Partita IVA 01927780369

Fiorano Modenese (MO) 01/07/13  
 Place and date of issue



Coem S.p.A.  
Via Cameazzo, N° 25  
41042 Fiorano Modenese (MO)  
05

300\_DOP\_Coem

**EN 14411:2012**

Dry-pressed ceramic tiles, with water absorption  $E_b > 10\%$ , for internal walls

<b>Reaction to fire</b>	A1 <sub>FL</sub>
<b>Release of dangerous substances, for:</b>	
- Cadmium	NPD
- Lead	NPD
<b>Bond strength/adhesion, for:</b>	
Cementitious adhesive, type C1	NPD
<b>Durability, for:</b>	
- Internal use:	Pass